




Universal transmitter with external power supply - 1 port RF 96 ST SW922 Vcc extern-NET Article no.: on request

Product features

- sWave.NET® wireless technology
- Cable-free - with cost savings for installation and maintenance
- Configurable online via wireless interface
- Simple operation and integration in existing ERP systems via Sensor Bridge
- High scalability - up to several hundred sensors in one application
- External power supply via M12 plug-in connector

Dimensions



General technical data

Applied standards

EN 60947-5-1, EN 61000-6-2, EN 61000-6-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 301 489-3, EN 300 220-2

Enclosure

thermoplastic, glass-fibre reinforced, shockproof, self-extinguishing UL 94 V-0

Tightening torque

M4 enclosure mounting screws: max 1.2 Nm
M2.5 cover screws: approx. 0.45 Nm

Degree of protection

IP67 (IEC/EN 60529), only with plugged cable

Voltage source

24 VDC

Connection

plug-in connector M12 x 1, 4-pole, A-coded

Ambient temperature

-20 °C ... +65 °C

Switching frequency

max. 5 Hz

Rated operating voltage range U_B

10 ... 30 VDC Pin 1 and Pin 3 plug-in connector M12

Rated insulation voltage U_i

75 VDC

Rated impulse withstand voltage U_{imp}

0.5 kV

Rated operating current I_e

2.5 mA

Standby current

15 μ A (if sensor is not connected)

Voltage drop $U_e - U_{out}$

1.5 V

Load current

max. 100 mA

Switching points

> 5 VDC (E1, E2)

Actuating time

min. 80 ms

Errors and omissions excepted.



Universal transmitter with external power supply - 1 port RF 96 ST SW922 Vcc extern-NET Article no.: on request

General technical data (contd.)

Wireless approvals

Japan:  ARIB STD-T108: 204-610002

Wireless technology

Frequency

916.5 MHz (Japan)

Data rate

66 kbps

Channel bandwidth

520 kHz

Modulation type

2-FSK

Protocol

sWave.NET®

Transmission power

< 1 mW


Wireless range

max. 150 m outdoors, max. 20 m indoors


Pin assignment / Power supply

M12 x 1


1 BN	+U _B
2 WH	NC
3 BU	-U _B
4 BK	NC



External switch contact



Sensors



Errors and omissions excepted.